



SHOWROOM LINE



## Finishing Products

# FINISHING WAX

## Protective wax for floors made of terracotta, stone, or concrete

**FINISHING WAX** is a self-polishing wax for natural stone, terracotta, parquet or natural wood, or concrete surfaces. The product seals the surface textures, creating a dirt-proof layer and making daily cleaning and maintenance much easier.

**FINISHING WAX** leaves the surface with a polished finish and it slightly enhances the original color of the material. It also stands out for its excellent dirt-proof action. The product is recommended on natural stone with a distressed, brushed, or fine sanded finish and can also be used on concrete, concrete tiles, and, cotto, terracotta, and porous surfaces in general.

### BENEFITS

- ✓ It enhances the shine and the color of the material
- ✓ It protects against dirt and staining agents
- ✓ It doesn't yellow overtime
- ✓ Good resistance to foot traffic

### USES

Suitable for indoor application.  
Suitable for Marble-cement agglomerate, Slate, Sandstone, Basaltina - Lava stone, Cementina, Concrete, Cotto, Granite, Wood, Limestone, Marble, Parquet or natural wood, Quartzite, Terracotta, Travertine

### COVERAGE

10/20 m<sup>2</sup>/l

### APPLICATION EQUIPMENT

Lambswool applicator

### APPLICATION STEPS

*Before applying the product it is necessary taking a preliminary test to evaluate the suitability of the product on an unexposed area or unused piece of material.*

#### Surface Preparation

- Carefully clean the surface, making sure to remove any dust or dirt present.
- Wait for the surface to be completely dry.
- Any surface in the premises not being treated must be protected.
- Apply the product on surfaces with a temperature within this range +5 | +40°C

#### Application

- On a dry and clean surface apply a thin and even layer of product making sure to evenly cover the whole surface. We recommend applying the product always in the same direction. When applying the product making sure to avoid leaving product build-ups.
- Se durante la fase di stesura della cera, si notassero degli accumuli in un settore sul quale si è già terminata la stesura del prodotto, non tentare di riuniformare lo strato di materiale: attendere la maturazione del primo strato di cera e solo successivamente si potrà intervenire per riuniformare l'aspetto della superficie.
- In caso di applicazione su superfici particolarmente assorbenti o rugose potrebbe risultare necessaria la stesura di un secondo strato di prodotto. Procedere in questo senso solamente dopo che la prima mano di prodotto sia perfettamente asciutta. Generalmente sono sufficienti circa 2-3 ore tra

MADE IN ITALY

100%



## SHOWROOM LINE

APPLICATION  
STEPS

- una mano e l'altra. Per applicare la seconda mano seguire le medesime modalità sopra indicate. Sugeriamo di applicare il secondo strato nel verso perpendicolare a quello seguito per la prima mano. Così facendo si realizzerà una applicazione "incrociata".
- **FINISHING WAX** è una cera autolucidante che, una volta terminata la sua applicazione, permette di ottenere uno spiccato effetto lucido. Nel caso in cui però si voglia aumentare ulteriormente la lucentezza della superficie, è possibile farlo mediante l'utilizzo di una monospazzola tradizionale munita di pad bianco o in di agnello. Attendere minimo 3-4 ore dalla maturazione della cera e procedere lavorando la superficie a secco e prolungando la spazzolatura fino a che non si sarà ottenuto un effetto soddisfacente. Intervenire con la spazzolatura meccanica permette inoltre di recuperare eventuali difetti estetici provocati dall'accumulo del prodotto in un determinato settore di superficie.

*Resume Surface Use*

The product dries withing 1-2 hours form the application. Resume surface use after 4-6 hours from the product application.

COMPLEMENTARY  
MAINTENANCE  
PRODUCTS

To maintain a surface treated with **FINISHING WAX** use the most suitable Faber cleaner, such as **NEUTRAL CLEANER** or **FLOOR CLEANER**, depending on the nature of the surface. To maintain the wax layer use **MAINTENANCE WAX** or **FINISHING WAX** diluted 1:5.

INSTRUCTIONS  
AND GUIDELINES

- Do not apply the product on wet or heated surfaces
- Do not apply the product on surfaces recently treated with acidic products
- When applying to recently laid or grouted surfaces, wait for the adhesive or grout to cure completely.
- Do not apply the product on outdoor surfaces
- Before applying the product it is necessary taking a preliminary test to evaluate its suitability

EQUIPMENT  
CLEANING

The equipment used can be cleaned with water

## PHYSICAL AND TECHNICAL INFORMATION

Formula	Liquid
Color	Typical
Odor	Caratteristico
pH	8,0 ± 0,5
Specific gravity at 20°C	1020 ± 10 g/l

## STORAGE

Keep the container tightly closed and store in a cool, dry place.

## SHELF LIFE

24 months in the original, sealed packaging, stored in a cool, dry place.

## PACKAGING

1 l bottles - 12 bottles per box  
5 l bottles - 4 bottles per box

MADE IN ITALY

100%

FABER CHIMICA SRL

60044 FABRIANO (AN) ITALY - VIA G. CERESANI 10 - LOC. CAMPO D'OLMO

PI-CF / VAT NUMBER 0100744021 - P: +39 0732 62 71 78

INFO@FABERSURFACECARE.COM - FABERSURFACECARE.COM



SHOWROOM LINE



**ACCIDENTAL SPILLS**

Soak up the product with an absorbent material (paper towels, sawdust, vermiculite, etc.) and dispose of it in the most suitable waste container.

**SAFETY**

When applying the product, always use suitable personal protective equipment and follow the instructions on the product safety data sheet with care.

Rev3.0 – 12/09/2022

**This technical data sheet supersedes all previous versions. Always refer to the latest version of the data sheet, available on [www.fabersurfacecare.com](http://www.fabersurfacecare.com) site. Faber Chimica reserves the right to update and/or modify the data and information contained in the datasheet.**

*The information in this data sheet is based on our wide experience in technical and operational research. In any case, you should always make a preliminary test to verify the suitability of the product for the intended use and the type of material on which it will be applied. The information and the suggestions can't be construed as a commitment or result in our responsibility as the conditions and method of use of the product cannot be controlled by us. Therefore Faber Chimica Srl disclaims any liability concerning the use of such data and suggestions.*

MADE IN ITALY

100%