



PROFESSIONAL LINE



Protective Treatments

AS 930

Solvent-based, stain-resistant treatment with a shiny wet-look effect, for antiqued marble and natural stone.

AS 930 is a solvent-based, stain-resistant treatment that provides a shiny wet-look effect on marble, granite, or antiqued stone. The product can also be used on absorbent artificial surfaces with a rough, textured finish.

AS 930 brings out the characteristic veins of the material to which it is applied, enhancing the natural color while providing stain-resistant properties. The product protects against dirt build-ups increasing the resistance against foot traffic and making maintenance operations easier.

BENEFITS

- ✓ UV resistant
- ✓ High stain-resistant properties
- ✓ Increases the resistance to foot traffic
- ✓ Makes maintenance easier

USES

This product can be used on both indoor and outdoor surfaces. Suitable for use on Marble-cement agglomerate, Slate, Sandstone, Concrete Tiles, Concrete, Cotto, Granite, Marble, Exposed brickwork, Reconstituted (eco) stone, Porphyry, Quarzite, Terracotta, and Travertine. The product can be applied on the above surfaces, with rough, antiqued or cleft finishes.

COVERAGE

15/20 m²/l

APPLICATION EQUIPMENT

Brush, Lambswool applicator, Roller

APPLICATION STEPS

Surface preparation

- Carefully clean the surface, making sure to remove any dust or dirt present.
- Never apply **AS 930** to wet or damp surfaces.
- Apply **AS 930** to surfaces with a temperature between +5 and +40°C
- Any surfaces in direct proximity not being treated must be protected.

Application

- Apply a thin light coat of product to a clean, dry surface with the preferred tool, making sure to create an even layer to cover the whole surface being treated and trying to treat the area in the shortest time possible so that the film can cure spontaneously without any imperfections.
- If there are any differences in shine during the drying stages, due to the different degrees of absorption on the surface, do not try to even out the product; wait for it to cure completely (about 4-6 hours) and then repeat the application following the same process as described

Drying Time

The product dries quickly, it might take up to 45 minutes.

Resume Surface Use

Resume the use of the surface after 4-6 hours from the application



PROFESSIONAL LINE



MAINTENANCE PRODUCTS

- For the daily cleaning of a surface treated with **AS 930**, we recommend: **NEUGEL**
- For heavy-duty cleaning of a surface treated with **AS 930**, we recommend: **FABER 30**
- To perform a double wax stripping we recommend using **DEC 21** and/or **DECERA P**

INSTRUCTIONS AND GUIDELINES

- Never apply the product to wet or damp surfaces, polished surfaces, and dirty surfaces.
- If the product is applied as a stain-resistant treatment on a material that has already been primed with a high-penetrating water-repellent sealer, wait for it to dry completely before applying **AS 930**
- Do not apply the product to overly heated surfaces.
- Do not apply the product when there is an imminent risk of rain or frost, or in presence of mist, fog, or high levels of humidity.
- Apply the product to surfaces with a temperature of between +5 and +40°C
- After applying a layer of **AS 930**, leave it to cure without touching it before it is completely dry.
- When applying to recently laid or grouted surfaces, wait for the adhesive or grout to cure completely.
- Before applying the product to the whole surface, it is advisable to test a small, unexposed area or unused piece to check its suitability for use.

EQUIPMENT CLEANING

At the end of the application, the equipment used can be washed using water spirit.

PHYSICAL-TECHNICAL DATA

Formula	Liquid
Color	Clear
Odor	Solvent
Specific gravity a 20°C	930 ± 10 g/l

STORAGE

Keep the container tightly closed and store in a cool, dry place.

SHELF LIFE

24 months in the original, sealed packaging, stored in a cool, dry place.

PACKAGING

1 l bottles – 12 bottles per box
5 l bottles – 4 bottles per box

SAFETY

When applying the product, always use suitable personal protective equipment and follow the product safety data sheet instructions with care.

Revisione 5.0 – 17/10/2022

This technical data sheet supersedes all previous versions. Always refer to the latest version of the data sheet, available on www.fabersurfacecare.com site. Faber Chimica reserves the right to update and/or modify the data and information contained in the datasheet.

The information in this data sheet is based on our wide experience in technical and operational research. In any case, you should always make a preliminary test to verify the suitability of the product for the intended use and the type of material on which it will be applied. The information and the suggestions can't be construed as a commitment or result in our responsibility as the conditions and method of use of the product cannot be controlled by us. Therefore Faber Chimica Srl disclaims any liability concerning the use of such data and suggestions.