

STONE COLOUR ENHANCER

Colour-enhancing, stain-proof impregnator
with semi-polished wet-look finish, for all absorbent surfaces.



STONE COLOUR ENHANCER is a solvent-based, colour-enhancing and stain-proof impregnating agent that penetrates the surface, leaving a semi-polished wet-look finish and ensures great protection against stains on all medium-absorbent materials with non-polished finish. The formulation of **STONE COLOUR ENHANCER** gives treated material a semi-polished wet-look finish, boosting tone and colour, and enhancing the aesthetics of the surface. This product also stands out for its excellent water-repellence and stain-proof qualities, which offer effective protection against stains, and the damaging effects of water.

STONE COLOUR ENHANCER also makes routine surface maintenance easier, as it limits a surface's ability to trap dirt, preventing dirt and stains from penetrating below the surface and attaching to the material. **STONE COLOUR ENHANCER** is ready to use and quick and easy to apply. It is suitable for all types of absorbent material and can be used indoors and outside. **STONE COLOUR ENHANCER** is not suitable for use on non-absorbent materials or on materials with a polished finish

CHARACTERISTICS AND BENEFITS

- ✓ Strong colour-enhancing capacity
- ✓ Leaves surfaces stain proof
- ✓ Enhances the material's tone and colour
- ✓ Ultra resistant over time
- ✓ Excellent water- and oil-repellent characteristics
- ✓ Resistant to UV rays
- ✓ Will not yellow over time
- ✓ Adds a semi-polished finish
- ✓ Also suitable for application outdoors.

USES

This product **can be used** on both indoor and outdoor surfaces.

Suitable for use on: Cement-marble agglomerate, Slate, Sandstone, Basaltina - Lava rock, Cementine, Cotto, Granite, Limestone, Marble, Reconstituted (eco) stone, Porphyry, Quartzite, Terracotta, Travertine, and Tuff

COVERAGE

10-15 m²/l according to the absorption level of the surface being treated

APPLICATION EQUIPMENT

Brush, roller, lambswool applicator, cloth



Protectors

STONE COLOUR ENHANCER - Colour-enhancing, stain-proof impregnator with semi-polished wet-look finish, for all absorbent surfaces



APPLICATION STEPS

Preparing and cleaning the surface

1. Carefully clean the surface, making sure to remove any dust or dirt present.
2. Wait for the surface to be treated to be completely dry.
3. Any adjacent surfaces not being treated with the product must be protected.

Application

Before applying the product to the whole surface, always test a small, unexposed area or unused piece to check its suitability for use.

4. Apply a thick, even layer of product to cover the whole surface being treated, using the tools of choice. Make sure to create a layer that is as seamless and even as possible.
5. About 10 minutes from application, proceed to redistribute product residues and excesses on the surface. This operation needs to be meticulously carried out until the surface is completely dry.
6. If applying the product to more absorbent surfaces, apply a second coat about 1-2 hours after the first, following the same procedure described above.

Drying time

Surfaces will be dry about 1-2 hours from product application.

Opening to floor traffic

When used on floor surfaces, wait at least 6 hours before opening the floor to foot traffic.

COMPLEMENTARY CLEANING AND MAINTENANCE PRODUCTS

After treatment with STONE COLOUR ENHANCER, maintain the surface clean with the product most suitable Faber product, such as NEUTRAL CLEANER or FLOOR CLEANER or, to be chosen according to the surface characteristics.

INSTRUCTIONS AND GUIDELINES

- Never apply the product to a wet surface
- Do not apply the product to overly heated surfaces
- When applying to recently laid or grouted surfaces, wait for the adhesive or grout to cure completely.
- If used after a water-repellent primer has been applied, wait for this treatment to cure fully before applying STONE COLOUR ENHANCER
- Before applying the product to the whole surface, it is advisable to test a small, unexposed area or unused piece to check its suitability for use.

EQUIPMENT CLEANING

At the end of application, the equipment used can be cleaned using white spirit.

SAFETY

When applying the product, always use suitable personal protective equipment and follow the instructions on the product safety data sheet with care.



Protectors

STONE COLOUR ENHANCER - Colour-enhancing, stain-proof impregnator with semi-polished wet-look finish, for all absorbent surfaces



PHYSICAL AND TECHNICAL INFORMATION

Aspetto:	Liquido
Colore:	Trasparente
Odore:	Ragia
Peso specifico a 20°C	840 ± 10 g/l
Punto di infiammabilità (ASTM D56)	30°C vaso aperto

STORAGE

Keep the container tightly closed and store in a cool, dry place.

SHELF LIFE

24 months in the original, sealed packaging, stored in a cool, dry place.

ACCIDENTAL SPILLS

Soak up the product with an absorbent material (paper towels, sawdust, vermiculite, etc.) and dispose of it in the most suitable waste container.

PACKAGING

- 1 l bottles - 12 bottles per box
- 5 l cans – 4 cans per box

HAZARD IDENTIFICATION



H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.
EUH066	Repeated exposure may cause skin dryness or cracking.
P210	Keep away from heat/sparks/open flames/hot surfaces. — No smoking.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P331	Do NOT induce vomiting.
P303+P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P501	Dispose of contents/container to special waste collecting point

Version 4.0 – 01/09/2016

This technical data sheet supersedes all previous versions. Always refer to the latest version of the data sheet, available on www.fabersurfacecare.com site. Faber Chimica reserves the right to update and / or modify the data and information contained in the data sheet.

The information in this data sheet is based on our wide experience in technical and operational research. In any case you should always make a preliminary test to verify the suitability of the product for the intended use and the type of material on which it will be applied. The information and the suggestions can't be construed as a commitment or result in our responsibility as the conditions and method of use of the product cannot be controlled by us. Therefore Faber Chimica Srl disclaims any liability with regard to the use of such data and suggestions.

FABER CHIMICA SRL – VIA G.CERESANI, 10 – LOC.CAMPO D'OLMO – 60044 – FABRIANO (AN) – ITALY

Phone: +39 0732 627178 | Fax: +39 0732 22935 | Email: info@faberchimica.com

Pag. 3 di 3



FABERSURFACECARE.COM

