

PROFESSIONAL LINE



Finishing Treatments

B1 920

Water-based easy to apply polishing wax for vertical surfaces

B1 920 is a resin-wax water-based formulated to polish vertical and non-walkable surfaces.

B1 920 creates a thin protective layer that protects the surface enhancing the look and the shine of the material and making daily maintenance easier.

B1 920 makes the polishing of vertical surfaces easier.

BENEFITS

- Ideal for vertical surfaces
- ✓ Suitable for surfaces that have been waxed before
- ✓ It makes daily maintenance easier
- ✓ It enhances the shine and look of the surface

USES

This product can be used indoor.

Suitable for use on Granite, Marble, Travertine, and Limestone.

COVERAGE

25/35 m²/l - initial application 30/50 m²/l - maintenance

APPLICATION EQUIPMENT

Product application:

Brush, Lambswool applicator, Roller, Cloth

Polishing:

Single disk machine or hand polisher

APPLICATION STEPS

Surface preparation

- Carefully clean the surface, making sure to remove any dust or dirt present.
- Never apply B1 920 to wet or damp surfaces.
- Apply B1 920 to surfaces with a temperature of between +5 and +40°C
- Any adjacent surfaces not being treated with the product must be protected.
- We recommend working on small areas in order to polish them easily with the orbital or flexible polisher.
- Before proceeding with to apply the product, we recommend pouring B1
 920 into a spray applicator bottle with a wide nozzle. This serves to apply the product to the surface, notably speeding up the work process.

Application

Before applying the product is necessary to take a preliminary test on an unexposed area or unused piece of material to check the product's suitability.

- Shake the bottle thoroughly and spray a small amount of product directly onto the area to be treated. Generally, about 2-3 sprays of the product are enough for treating small sections of an area.
- As soon as the product has been applied, proceed to polish the surface.
 This operation can be carried out manually on small surfaces, using a wool-cotton cloth, white or wire wool pad. In the case of larger areas, we recommend using a tool such as the orbital or flexible polisher, complete with a white or lambskin pad, steel-wool pad, or similar.



PROFESSIONAL LINE



APPLICATION STEPS

- Pass the polisher being sure to use concentric movements so as to distribute the product evenly over the whole section being treated.
- Work the surface, brushing or polishing until all excess has been removed (the Spray Buffing technique) and the end result is both even and polished.
- Pass on to the next section, repeating the polishing treatment process as described above.
- After treating all of the surface areas, remove any steel wool residues from the surface using a dry cloth.

Resume Surface Use

After the product is completely dry, no further waiting time is necessary.

MAINTENANCE PRODUCTS

 To perform a double wax stripping we recommend using DEC 21 and/or DECERA P

INSTRUCTIONS AND GUIDELINES

- Never apply the product to wet or damp surfaces.
- Do not apply the product to overly heated surfaces.
- Do not apply the product on floors
- Apply the product to surfaces with a temperature of between +5 and +35°C
- When applying to recently laid or grouted surfaces, wait for the adhesive or grout to cure completely.
- Before applying the product to the whole surface, it is advisable to test a small, unexposed area or unused piece to check its suitability for use.

EQUIPMENT CLEANING

At the end of the application, the equipment used can be washed using water

PHYSICAL-TECHNICAL DATA

Formula	Liquid
Color	White
Odor	Sweet
Specific gravity a 20°C	9 ± 0.5
Flash Point (ASTM D 56)	1000 ± 5 g/l

STORAGE Keep the container tightly closed and store in a cool, dry place.

SHELF LIFE 36 months in the original, sealed packaging, stored in a cool, dry place.

PACKAGING 1 | bottles – 12 bottles per box

5 I bottles – 4 bottles per box

SAFETY When applying the product, always use suitable personal protective equipment

and follow the product safety data sheet instructions with care.

Rev. 4.0 - 17/10/2022

This technical data sheet supersedes all previous versions. Always refer to the latest version of the data sheet, available on www.fabersurfacecare.com site. Faber Chimica reserves the right to update and/or modify the data and information contained in the datasheet.

The information in this data sheet is based on our wide experience in technical and operational research. In any case, you should always make a preliminary test to verify the suitability of the product for the intended use and the type of material on which it will be applied. The information and the suggestions can't be construed as a commitment or result in our responsibility as the conditions and method of use of the product cannot be controlled by us. Therefore Faber Chimica Srl disclaims any liability concerning the use of such data and suggestions.