

GRAFFITI REMOVER

Product specifically to remove paint, graffiti, inks and epoxy residues from surfaces made of tile or natural stone.



GRAFFITI REMOVER is a product specifically to remove graffiti, paint and permanent inks from surfaces. Thanks to its thick, viscous consistency, the product is easy to apply, even on vertical surfaces, making it possible to effectively clean graffiti or paint and stains in general from walls.

GRAFFITI REMOVER is also effective on hardened epoxy grout residues, generally from incorrect or absent post-installation cleaning process. The product is quick and easy to apply, directly on the area to be treated, and it is fast-acting as well as definitively removing graffiti and paint residues without altering the original appearance of the material in any way.

CHARACTERISTICS AND BENEFITS

- ✓ **Excellent power to break down paint and inks**
- ✓ **Quick and easy application**
- ✓ **Will not ruin treated surfaces**
- ✓ **Suitable for use on vertical surfaces**
- ✓ **Effective on epoxy residues**

USES

This product **can be used** on both indoor and outdoor surfaces.

Suitable for use on: Steel, Aluminium, Marble-cement agglomerate, Marble-resin agglomerate, Quartz resin agglomerate, Slate, Sandstone, Basaltina - Lava stone, Molten basalt, Cementina, Concrete, Craquelé ceramics, Glazed ceramics, Clinker, Cotto, Granite, Lapped porcelain stoneware, Polished porcelain stoneware, Natural porcelain stoneware, Textured porcelain stoneware, Cement grout, Limestone, Marble, Exposed brick, Metal, Parquet and natural wood, Reconstituted stone (Eco stone), Porphyry, Quarzite, Terracotta, Travertine, Tuff, and Glass

COVERAGE

N.A.

APPLICATION EQUIPMENT

Brush, Spatula, Direct application to stains

APPLICATION STEPS

Preparing and cleaning the surface

1. Carefully clean the surface, making sure to remove any dust or rough dirt present.
2. Never use GRAFFITI REMOVER on wet surfaces; make sure that the surface to be treated is dry or at most, only slightly damp.
3. Do not apply GRAFFITI REMOVER to overly heated surfaces. We recommend applying the product during the coolest periods of the day.



GRAFFITI REMOVER - Product specifically to remove paint, graffiti, inks and epoxy residues from surfaces made of tile or natural stone.



Application

4. The product is for use without dilution. Pour the undiluted product straight onto the surface being treated. Use a brush, spatula or if simpler, pour directly onto the surface, covering it completely with a thick layer of product.

5. Leave the product to act on the surface until the synthetic layer to be removed has broken down completely. The necessary time depends on the type of material being removed and the absorption level of the surface being treated.

Although all cases have different characteristics that may require specific and different timeframes, generally the time required to dissolve the synthetic surface layers can be summed up as follows:

- For non-absorbent surfaces or light residues: between 10 and 20 minutes;
- For absorbent surfaces or stubborn residues: from 1 to 4 hours;
- For particularly stubborn residues or defacements: from 12 to 24 hours.

In case of interventions requiring longer periods of time, we recommend applying a sufficiently thick layer of product to avoid having to add more in the event that it dries too quickly.

6. After the set period of time, proceed to remove the product and its residues. To remove GRAFFITI REMOVER it is possible to use absorbent paper or cloths in case of small surfaces, soaking up and removing residues until the surface is completely clean. Wipe the surface with a slightly damp cloth and wait for it to dry thoroughly before assessing the stain removal results. In case of medium or large surfaces, remove all residues with a broom and absorbent rags or a damp mop, until all excesses have been completely eliminated. Wipe the surface with a slightly damp cloth or mop and wait for it to dry thoroughly before assessing the stain removal results.

If the finished result is not totally satisfactory, repeat the product application process as described above.

Opening to floor traffic

7. After rinsing the surface with water, wait for the floor to dry completely before opening to foot traffic.

COMPLEMENTARY CLEANING AND MAINTENANCE PRODUCTS

After treating with GRAFFITI REMOVER assess the possibility to apply a stainproof primer, such as ANTIGRAFFITI or MARBLE & GRANITE PROTECTOR or AQUA TREATMENT, which needs to be chosen according to the characteristics of the surface. Keep the surface clean with the most suitable Faber product, such as NEUTRAL CLEANER or FLOOR CLEANER, to be selected according to the characteristics of the surface.



Stain removers

GRAFFITI REMOVER - Product specifically to remove paint, graffiti, inks and epoxy residues from surfaces made of tile or natural stone.



INSTRUCTIONS AND GUIDELINES

GRAFFITI REMOVER must only be used alone. NEVER mix it with other chemicals.

- Never apply the product to wet or excessively damp surfaces.
- Do not apply the product to overly heated surfaces.
- Do not apply the product when there is an imminent risk of rain or frost, or in the presence of mist.
- While applying the product to the surface concerned it must not be exposed to direct sunlight.
- Apply the product to surfaces in temperatures of between +5 and +40°C
- When using on recently laid or grouted surfaces, wait for the grout to cure completely.
- Take care not to use the product on grout widths filled with epoxy grout.
- Before applying the product to the whole surface, it is advisable to test a small, unexposed area or unused piece to check its suitability for use.

EQUIPMENT CLEANING

At the end of application, the equipment used can be cleaned using white spirit.

SAFETY

When applying the product, always use suitable personal protective equipment and carefully follow the instructions on the product safety data sheet.

PHYSICAL AND TECHNICAL INFORMATION

Aspect:	Gel
Colour:	Blu
Odour	Solvent
Flash Point (ASTM D 56)	21°C
Specific Gravity at 20°C	890 ± 10 g/l

STORAGE

Keep the container tightly closed and store in a cool, dry place.

SHELF LIFE

24 months in the original, sealed packaging, stored in a cool, dry place.

ACCIDENTAL SPILLS

Soak up the product with an absorbent material (paper towels, sawdust, vermiculite, etc.) and dispose of it in the most suitable waste container.

PACKAGING

- 750 ml bottles



HAZARD IDENTIFICATION



H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
EUH066	Repeated exposure may cause skin dryness or cracking.
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read label before use.
P210	Keep away from heat/sparks/open flames/hot surfaces. — No smoking.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

Version 2.0 – 17/10/2016

This technical data sheet supersedes all previous versions. Always refer to the latest version of the data sheet, available on www.fabersurfacecare.com site. Faber Chimica reserves the right to update and / or modify the data and information contained in the data sheet.

The information in this data sheet is based on our wide experience in technical and operational research. In any case you should always make a preliminary test to verify the suitability of the product for the intended use and the type of material on which it will be applied. The information and the suggestions can't be construed as a commitment or result in our responsibility as the conditions and method of use of the product cannot be controlled by us. Therefore Faber Chimica Srl disclaims any liability with regard to the use of such data and suggestions.

