

Protective

P 211/B

Colour enhancer stain proof impregnator solvent-based



P 211/B is a solvent based impregnator with wet look. The product use is intended to avoid acidifying both a sandblasted and a rough surface. Stones treated with **P 211/B** take a warm shade and the natural veins of the material are enhanced. Besides offering excellent water- and oil-repellent features to the most compact surfaces, it allows vapor transpiration.

CHARACTERISTICS AND BENEFITS

- ✓ Excellent stain proof capacity
- ✓ Provides hydro-repellency to the surface
- ✓ Provides oleo-repellency to the surface
- ✓ Wet look
- ✓ UV Resistant
- ✓ No yellowing

USES

For exteriors and interiors.

Marbles, Travertines and Granites polished, brushed or finely honed. Slate, cobblestone and several compact natural stones.

COVERAGE

15/20 m²/lt

APPLICATION EQUIPMENT

Brush, Roller, Lambswool applicator

APPLICATION

Test on a small area before proceeding, so to ensure product suitability and final result.

Apply P211/B to a dry and clean surface with a brush, a roller, a lamb's wool or sprayer. If more than one coat is necessary, due to the high absorption capacity, wait until the first one will have dried for 30 minutes at least before applying the second coat.

Wait a curing time of about 10 minutes for solvent evaporation (depending on the material absorption capacity), then remove the residue with a scrubbing brush or with a monobrush and cotton cloth or blotting paper.

After having carefully removed the residue, wait at least 4 to 6 hours before reopening the area to foot traffic.

Never apply the product on wet surfaces or onto surfaces that are directly exposed to sun rays during the application phase.

EQUIPMENT CLEANING

At the end of application, the equipment used can be washed using white spirit.

SAFETY

When applying the product, always use suitable personal protective equipment and follow the instructions on the product safety data sheet with care.



Protective

P 211/B

Colour enhancer stain proof impregnator solvent-based



LINEA
PROFESSIONALE

PHYSICAL AND TECHNICAL INFORMATION

Aspect:	Liquid
Color:	Transparent
Odour	Mineral Spirit
Specific Gravity (20°C)	825 ± 10 g/lit
Flashing point (ASTM D 56)	30°C open vase

STORAGE

Keep the container tightly closed and store in a cool, dry place.

SHELF LIFE

24 months in the original, sealed packaging, stored in a cool, dry place.

PACKAGING

- 1 lt bottles (12 per carton) - 5 lt cans (4 per carton)



HAZARD IDENTIFICATION

R10	Flammable
R65	Harmful: may cause lung damage if swallowed
R66	Repeated exposure to vapors may cause dryness or cracking
S2	Keep out of the reach of children
S16	Keep away from sources of ignition and – No smoking
S23	Do not breathe fumes or vapours
S24	Avoid contact with the skin
S25	Avoid contact with eyes
S37	Use suitable gloves

Version 2.1 – 11/10/2017

This technical data sheet supersedes all previous versions. Always refer to the latest version of the data sheet, available on www.fabersurfacecare.com site. Faber Chimica reserves the right to update and / or modify the data and information contained in the data sheet.

The information in this data sheet is based on our wide experience in technical and operational research. In any case you should always make a preliminary test to verify the suitability of the product for the intended use and the type of material on which it will be applied. The information and the suggestions can't be construed as a commitment or result in our responsibility as the conditions and method of use of the product cannot be controlled by us. Therefore Faber Chimica Srl disclaims any liability with regard to the use of such data and suggestions.

