

### PROFESSIONAL LINE



#### Honing & Polishing

### PORCELAIN RESTORATION CREAM

# Water-based cream to restore full-body polished porcelain tiles and glazed polished porcelain tiles

**PORCELAIN RESTORATION CREAM** is a water-based cream to be used to restore defects on full-body polished porcelain tiles, glazed polished porcelain tiles, and glazed surfaces in general. The product has an ultra-fine micro-abrasive effect that will restore flaws and defects on the surfaces such as:

- Slight abrasions
- Scratches
- Dulness
- Disuniformity
- General wear

**PORCELAIN RESTORATION CREAM** acts without changing the original look of the surface and it's also part of our GLAZED POLISHED TILES RESTORATION SYSTEM.

#### **BENEFITS**

- Versatile solution
- Restores the original appearance of the material without spoiling the surface
- ✓ Even looking results
- Water-based product.
- ✓ No layering defects

### **USES**

This product can be used on both indoor and outdoor surfaces.

This product is suitable for use on Full-body polished porcelain tiles, Glazed polished porcelain tiles (Lappato), Glazed surfaces

#### **COVERAGE**

20/30 m<sup>2</sup>/kg

## APPLICATION EQUIPMENT

Single disc machine with at least 1.5 HP; manual rotary brush.

Faber Chimica can supply the WARRIOR single disc machine, which has a power of 2.2 HP and is optimized for the correct application of any product.

## APPLICATION STEPS

#### Surface preparation

- Carefully clean the surface, making sure to remove any dust or dirt present. We suggest using our **DETERFUG** or our **FABER 30**, depending on the nature of the dirt and the surface type.
- We suggest applying the product on surface sections of 2 m2 at a time.
- Apply the product to surfaces with a temperature of between +5 and +40°C
- Any adjacent surfaces not being treated with the product must be protected.

#### **Application**

Before applying the product is necessary to take a preliminary test on an unexposed area or unused piece of material to check the product's suitability.

• Shake the bottle well before use and pour 2/3 spoonful of product onto the surface to be treated. This amount is sufficient to treat a surface area of about 2 m<sup>2</sup>.



### PROFESSIONAL LINE



# APPLICATION STEPS

- Add a small amount of water to the cream. As a rough guide, each spoonful of product requires around 1 spoonful of water.
- As soon as the water has been added to the cream, proceed to apply it to the surface using the single disc machine, fitted with a white pad, and set to between 150 and 200 r.p.m. Continue with the single disc machine, taking care to cover the whole surface area evenly with the cream. Try to pass over each section of the floor the same number of times.
- During the application process, the mix must maintain its creamy consistency, and therefore, if it should become too dry, gradually add some drops of water.
- Continue to pass over the surface with the polisher until the result is as required. This is easy to check during application by removing a small area of product using a squeegee mop or similar and checking the surface finish.
- Once the required result has been achieved, vacuum or remove any residues from the surface and rinse with plenty of clean water.

Generally, **PORCELAIN RESTORATION CREAM** will restore the surface within 15-25 passages, but always checks depending on the type of surface

#### Resuming the surface use

After carefully removing any residues and rinsing the surface with water, the floor can be opened for use.

# MAINTENANCE PRODUCTS

- For the daily maintenance of a surface treated with PORCELAIN RESTORATION CREAM, we recommend: ALGAFLOOR
- For heavy-duty cleaning of a surface treated with **PORCELAIN RESTORATION CREAM**, we recommend **FABER 30** or **DETERFUG**, according to the type of dirt and the material to be cleaned.

# INSTRUCTIONS AND GUIDELINES

- Do not allow the product to dry during the application process. Frequently check consistency and add water as needed to return the product to its creamy state.
- Never apply the product to a wet surface
- Do not apply the product to overly heated surfaces
- Apply the product to surfaces with a temperature of between +5 and +40°C
- When applying to recently laid or grouted surfaces, wait for the adhesive or grout to cure completely.
- Before applying the product to the whole surface, it is advisable to test a small, unexposed area or unused piece to check its suitability for use.

# **EQUIPMENT CLEANING**

At the end of application, the equipment used can be washed using water.

#### PHYSICAL-TECHNICAL DATA

Formula	Cream
Color	Light Blue
Odor	Lightly Scented
pH:	$8.5 \pm 0.5$

**STORAGE** 

Keep the container tightly closed and store in a cool, dry place.

SHELF LIFE

36 months in the original, sealed packaging, stored in a cool, dry place.



### **PROFESSIONAL LINE**



PACKAGING 250 ml Bottle – 12 bottles per box

1 kg Bottle – 12 bottles per box 5 kg Bottle – 4 bottles per box

SAFETY When applying the product, always use suitable personal protective equipment

and follow the product safety data sheet instructions with care.

Revisione 2.0 - 05/06/2024

This technical data sheet supersedes all previous versions. Always refer to the latest version of the data sheet, available on www.fabersurfacecare.com site. Faber Chimica reserves the right to update and/or modify the data and information contained in the datasheet.

The information in this data sheet is based on our wide experience in technical and operational research. In any case, you should always make a preliminary test to verify the suitability of the product for the intended use and the type of material on which it will be applied. The information and the suggestions can't be construed as a commitment or result in our responsibility as the conditions and method of use of the product cannot be controlled by us. Therefore Faber Chimica Srl disclaims any liability concerning the use of such data and suggestions.