

EPOXY CLEANER

Alkaline cleaner specific for after setting washing of epoxy grouts and for the removal of epoxy patina or residues



EPOXY CLEANER is an alkaline-based cleaner specifically developed to remove residues and films from grouting and sealing operations carried out using seals or epoxy-based products, quickly and easily.

The product can be used for end-of-installation cleaning as well as to remove film or stains caused through incorrect or lack of cleaning once installation has been finished. **EPOXY CLEANER** is also extremely effective on epoxy residues that have been there for some time.

EPOXY CLEANER acts quickly and easily, even when used on surfaces that are particularly difficult to clean, such as low-thickness materials or those with a micro-textured surface finish.

Its mild but effective formula makes it ideal for use on acid-sensitive surfaces since it will not cause corrosion or aggression. **EPOXY CLEANER** is also particularly effective for the removal of synthetic residues, even if stubborn and have been there for some time, such as graffiti, paint and enamels.

CHARACTERISTICS AND BENEFITS

- ✓ Excellent **power to break down residues** and **epoxy patinas**
- ✓ **Top-level cleaning power**
- ✓ **Gentle on materials and on grout**
- ✓ **Fast acting**
- ✓ **Quick and easy application**
- ✓ **Will not attack treated materials**

USES

This product **can be used** on both indoor and outdoor surfaces.

Suitable for use on: Marble-cement agglomerate, Marble-resin agglomerate, Marble-quartz agglomerate, Slate, Sandstone, Basaltina - Lava stone, Molten basalt, Cementina, Concrete, Glazed ceramics, Clinker, Cotto, Granite, Lapped porcelain stoneware, Polished porcelain stoneware, Natural porcelain stoneware, Textured porcelain stoneware, Limestone, Marble, Reconstituted stone (Eco stone), Porphyry, Quarzite, Terracotta, Travertine, Tuff

COVERAGE

N.A.

APPLICATION EQUIPMENT

Cloth, mop, single-disc machine



Cleaners

EPOXY CLEANER

Alkaline cleaner specific for after setting washing of epoxy grouts and for the removal of epoxy patina or residues



APPLICATION STEPS

Preparing and cleaning the surface

1. Before proceeding to wash the surface with Epoxy Cleaner, it is advisable to clean away any surface residues, such as dust, debris and coarse dirt, using a broom or a vacuum cleaner,

We recommend treating small areas of the surface at a time. The size of the area to be treated individually should be decided according to the absorption level of the material.

When applying to highly absorbent surfaces, such as cotto or terracotta, it is necessary to work on an area of no more than about 4-5 sq. m, to ensure that the product does not penetrate the surface completely, which would prevent it from carrying out its function. When applying to low-absorption surfaces, such as stoneware or ceramic tiles, the treated area may be larger, according to the requirements and the capability of the operator.

Application

2. This product is applied undiluted

3. Apply the product to the surface, covering the whole area being cleaned and distributing it evenly and vigorously with a single-disc machine or large brush.

4. Leave the product to work for about 10-15 minutes for soft residues, 20-30 minutes in case of stubborn or aged residues, helping its dissolving action on the material by passing over with a single-disc machine or large brush at more or less regular time intervals, according to the difficulty in removing the residues that need to be dissolved. This will boost the dissolving action of the product and give you better results.

When applied to particularly absorbent surfaces, while working with the product, it may be necessary to pour some more onto the surface, to compensate for the product absorbed by the material. For the best possible results, it is important for the surface to be completely covered by a fine layer of product throughout the treatment.

This operation can be carried out using a more or less abrasive disc or brush, to be selected according to the type of material and the type of dirt or treatment being removed. White pad: for less dirty or more compact surfaces, such as glazed ceramics, for example. Green or light blue pad for rough, unpolished surfaces such as cotto, terracotta, etc.

5. After the above amount of time, remove the cleaning residues by pouring a sufficient amount of clean water onto the surface to form an emulsion with the solution on the floor; distribute this evenly with the single-disc machine or brush, and then remove any excess. This operation is best performed with a liquid vacuum cleaner, although alternatively, the excess liquid can be absorbed with cloths or absorbent paper towels.

6. After removing the residues, rinse the surface thoroughly using clean water. If the results are not completely satisfying, repeat the operation, following the steps above.



Cleaners

EPOXY CLEANER

Alkaline cleaner specific for after setting washing of epoxy grouts and for the removal of epoxy patina or residues



Opening to floor traffic

After rinsing the surface with water, the floor can be opened for use as soon as it is dry. When applying the treatment again, it is necessary to wait for the surface to be completely dry, all the way through. The amount of time for this will vary according to the type and absorption level of the material.

INSTRUCTIONS AND GUIDELINES

- Before applying the product to the whole surface, it is advisable to test a small, unexposed area or unused piece to check its suitability for use.
- When applying to recently laid or grouted surfaces, wait for the adhesive or grout to cure completely.
- Do not mix with other chemical compounds
- If the finished result is not totally satisfactory, repeat the process as described above.

EQUIPMENT CLEANING

At the end of application, the equipment used can be washed using water.

SAFETY

When applying the product, always use suitable personal protective equipment and follow the instructions on the product safety data sheet with care.

PHYSICAL AND TECHNICAL INFORMATION

Aspect:	Gel
Colour:	White
Odour:	Typical
pH:	11,0±0,5
Specific Gravity at 20°C	1120 ± 40 g/l

STORAGE

Keep the container tightly closed and store in a cool, dry place.

SHELF LIFE

24 months in the original, sealed packaging, stored in a cool, dry place.

PACKAGING

- 1 l bottles - 12 bottles per box



Cleaners

EPOXY CLEANER

Alkaline cleaner specific for after setting washing of epoxy grouts and for the removal of epoxy patina or residues



HAZARD IDENTIFICATION



H314	Causes severe skin burns and eye damage.
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P264	Wash hands thoroughly after handling.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing
P310	Immediately call a POISON CENTER/doctor.
P363	Wash contaminated clothing before reuse.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulation

Version 0.0 – 12/02/2018

This technical data sheet supersedes all previous versions. Always refer to the latest version of the data sheet, available on www.fabersurfacecare.com site. Faber Chimica reserves the right to update and / or modify the data and information contained in the data sheet.

The information in this data sheet is based on our wide experience in technical and operational research. In any case you should always make a preliminary test to verify the suitability of the product for the intended use and the type of material on which it will be applied. The information and the suggestions can't be construed as a commitment or result in our responsibility as the conditions and method of use of the product cannot be controlled by us. Therefore Faber Chimica Srl disclaims any liability with regard to the use of such data and suggestions.

