

MADE4STONE



Finishing Product

LIQUID WAX

Polishing and color-enhancing liquid wax for marble, granite, and natural stone

LIQUID WAX is a solvent-based fast-drying wax to polish and enhance the color of natural stone surfaces. It can be easily applied also along edges and surface irregularities.

The use of **LIQUID WAX** enhances the shade and brightness of the treated material. The product provides water and stain-resistant properties making daily maintenance operations easier.

BENEFITS

- ✓ Easy application
- ✓ It provides water and stain resistant properties
- ✓ It enhances the shade and brightness of the material
- ✓ It won't yellow overtime

USES

Suitable for indoor and outdoor application.

Suitable for Marble-concrete agglomerate, Slate, Basaltina - Lava stone, Concrete tiles, Clinker, Terracotta, Granite, Limestone, Marble, Quartzite,

Travertine

COVERAGE

15/25 m²/l

APPLICATION EQUIPMENT

Porduct application:

Lambswool applicator, roller, cloth

Porduct polishing:

Hand polisher, single disk machine

APPLICATION STEPS

Surface Preparation

- Thoroughly clean the surface making sure to remove all dust and dirt
- Do not apply LIQUID WAX on wet or humid surfaces
- In order to increase product penetration the surface can be heated
- · Protect all areas, not to be treated

Application

Before applying the product is necessary to take a preliminary test on an unexposed area or unused piece of material to check the product's suitability.

- On a clean and dry surface apply a thin and even layer of product using the preferred tool making sure to cover the whole surface.
- After 5-10 minutes, once the layer of wax has dried, start to polish the product.
- The polishing of LIQUID WAX can be done manually if the surface is small using a white pad. If the surface is large we recommend using a single disk machine or a hand polisher with a white pad.
- Polish the product on the surface in circular motions until all residues are gone. In the end, the shine must look even throughout the surface.

Drying time

The product dries guickly within 5-10 minutes of the application.

MAINTENANCE PRODUCTS

 To dewax a surface treated with LIQUID WAX we recommend: DEC 21 and/or DECERA P





MADE4STONE



INSTRUCTIONS AND GUIDELINES

- Do not apply on wet or humid surfaces
- Protect all areas not to be treated
- When applying to recently laid or grouted surfaces, wait for the adhesive or grout to cure completely.
- Before applying the product to the whole surface, it is advisable to test a small, unexposed area or unused piece to check its suitability for use.

EQUIPMENT CLEANING

At the end of the application, the equipment used can be washed using white spirit.

PHYSICAL-TECHNICAL DATA

Formula	Liquid
Color	Clear
Odor	Solvent
Specific gravity a 20°C	1510 ± 10 a/l

STORAGE Keep the container tightly closed and store in a cool, dry place.

SHELF LIFE 24 months in the original, sealed packaging, stored in a cool, dry place.

SAFETY When applying the product, always use suitable personal protective

equipment and follow the product safety data sheet instructions with

care.

Rev. 5.0 - 27/07/2023

This technical data sheet supersedes all previous versions. Always refer to the latest version of the data sheet, available on www.fabersurfacecare.com site. Faber Chimica reserves the right to update and/or modify the data and information contained in the datasheet.

The information in this data sheet is based on our wide experience in technical and operational research. In any case, you should always make a preliminary test to verify the suitability of the product for the intended use and the type of material on which it will be applied. The information and the suggestions can't be construed as a commitment or result in our responsibility as the product's conditions and method of use cannot be controlled by us. Therefore Faber Chimica Srl disclaims any liability concerning the use of such data and suggestions.