



MADE4STONE

**Finishing Product****LUX ONE****Self-polishing Solvent-Based Resin for Natural Stone**

LUX ONE is a solvent-based self-polishing resin. Its formula made of high-quality resins is recommended to polish natural stones that, due to their nature, are hard to polish mechanically such as edges, corners, and columns.

LUX ONE enhances the shade and brightness of the treated material. The product provides water-resistant properties making daily maintenance operations easier.

BENEFITS

- ✓ It provides stain-resistant and dirt-resistant protection
- ✓ It enhances the shade and brightness of the material
- ✓ It won't yellow overtime

USES

Suitable for Natural stone and absorbent materials. Particularly indicated for edges and corners that are difficult to polish mechanically. **Not suitable** for walkable surfaces.

COVERAGE

15/25 m²/l depending on the absorption level of the surface

APPLICATION EQUIPMENT

Product application:
Lambswool applicator, roller, cloth

APPLICATION STEPS**Surface Preparation**

- Thoroughly clean the surface making sure to remove all dust and dirt
- Do not apply **LUX ONE** on wet or humid surfaces
- Apply **LUX ONE** on surfaces with a temperature between +5 and +40°C
- Protect all areas, not to be treated

Application

Before applying the product is necessary to take a preliminary test on an unexposed area or unused piece of material to check the product's suitability.

- On a clean and dry surface apply a thin and even layer of product using the preferred tool making sure to cover the whole surface. No brushing necessary.
- Let the product dry for 10 to 15 minutes and evaluate the achieved result. If necessary, apply a second coat following the same procedure.

Drying time

The product dries completely within 30 minutes of the application. Wait at least 4 hours before resuming surface use.

INSTRUCTIONS AND GUIDELINES

- Do not apply on wet or humid surfaces
- Do not apply on heated surfaces
- Do not apply on walkable areas
- Protect all areas not to be treated
- Before applying the product to the whole surface, it is advisable to test a small, unexposed area or unused piece to check its suitability for use.

MADE IN ITALY

100%



MADE4STONE

**EQUIPMENT
CLEANING**

At the end of the application, the equipment used can be washed using white spirit.

PHYSICAL-TECHNICAL DATA

Formula	<i>Thick liquid</i>
Color	<i>Clear or milky depending on the temperature</i>
Odor	<i>Solvent</i>
Specific gravity a 20°C	<i>1360 ± 10 g/l</i>

STORAGE

Keep the container tightly closed and store in a cool, dry place.

SHELF LIFE

36 months in the original, sealed packaging, stored in a cool, dry place.

SAFETY

When applying the product, always use suitable personal protective equipment and follow the product safety data sheet instructions with care.

Rev. 5.0 – 27/07/2023

This technical data sheet supersedes all previous versions. Always refer to the latest version of the data sheet, available on www.fabersurfacecare.com site. Faber Chimica reserves the right to update and/or modify the data and information contained in the datasheet.

The information in this data sheet is based on our wide experience in technical and operational research. In any case, you should always make a preliminary test to verify the suitability of the product for the intended use and the type of material on which it will be applied. The information and the suggestions can't be construed as a commitment or result in our responsibility as the product's conditions and method of use cannot be controlled by us. Therefore Faber Chimica Srl disclaims any liability concerning the use of such data and suggestions.

MADE IN ITALY

100%

FABER CHIMICA SRL

60044 FABRIANO (AN) ITALY - VIA G. CERESANI 10 - LOC. CAMPO D'OLMO

PI-CF / VAT NUMBER 0100744021 - P: +39 0732 62 71 78

INFO@FABERSURFACECARE.COM - FABERSURFACECARE.COM