



MADE4STONE



Protective treatments

W-SHADE

Water-based, stain-resistant color-enhancing treatment with a matt finish for absorbing materials

W-SHADE is a water-based stain-resistant color-enhancing treatment. The product penetrates deep into the material enhancing the color without creating a film on the surface. **W-SHADE** is suitable for materials with a medium-high level of absorbency.

BENEFITS

- ✓ It provides high color-enhancing features
- ✓ It doesn't create a film on the surface
- ✓ It won't yellow overtime
- ✓ Water-based
- ✓ Great stain-resistant features

USES

Suitable for indoor and outdoor application.

Suitable for Marble-cement agglomerate, Marble-resin agglomerate, Quartz-resin agglomerate, Slate, Sandstone, Basaltina - Lava stone, Molten basalt, Cementine, Cement, Terracotta, Granite, Limestone, Marble, Reconstructed stone (Eco stone), Porphyry, Quartzite, Terracotta, Travertine, Tuff.

COVERAGE

15/20 m²/l

APPLICATION EQUIPMENT

Product application:

Lambswool applicator, roller, cloth

APPLICATION STEPS

Surface Preparation

- Thoroughly clean the surface making sure to remove all dust and dirt
- Do not apply **W-SHADE** on wet or humid surfaces
- Apply **W-SHADE** on surfaces with a temperature between +5 and +40°C
- Protect all areas not to be treated

Application

Before applying the product is necessary to take a preliminary test on an unexposed area or unused piece of material to check the product's suitability.


- On a clean and dry surface apply a thin and even layer of product using the preferred tool making sure to cover the whole surface.
- After 5-10 minutes from the application, before it is absorbed, proceed to even out the residues using the same tool used for the application. Make sure to distribute them evenly in order to achieve a seamless result.
- When applied to high-absorbing materials the product gets usually absorbed without leaving residues. If needed it is possible to apply a second coat making sure to wait at least 2-3 hours in between applications.
- When applied to more compact and less absorbing materials it is crucial to thoroughly remove all residues in order to avoid incurring the risk of creating an oily patina on the surface.
- The residue removal operations can be done after 20-30 minutes using a single disk machine equipped with a white pad or a wool pad.

MADE IN ITALY

100%



MADE4STONE



APPLICATION STEPS

- On smaller surfaces, it can be done mechanically using a hand polisher or by hand using a wool or cotton cloth.
- To maximize the efficacy and color enhancement of the treatment it is possible to wait up to 40-60 minutes to remove the residues to allow the product to penetrate deeply inside the material. When doing so the residue removal phase might be more complex to perform.

Drying time

The product dries quickly within 1-2 hours from the application.

Resume surface use

Resume surface use after 4-6 hours from the application.

MAINTENANCE PRODUCTS

- For the daily cleaning of a surface treated with **W-SHADE** we recommend: **NEUGEL** or **ALGAFLOOR** depending on the material
- For the heavy-duty cleaning of a surface treated with **W-SHADE** we recommend: **FABER 30** or **DETERFUG** depending on the material
- To dewax a surface treated with **W-SHADE** we recommend: **DEC 21** and/or **DECERA P** depending on the material

INSTRUCTIONS AND GUIDELINES

- Do not apply on wet or humid surfaces
- When used as a stain-resistant treatment on a surface previously treated with a water-resistant sealer, wait for the surface to be completely dry before applying **W-SHADE**
- Do not apply the product to overly heated surfaces
- Apply the product to surfaces with a temperature of between +5 and +40°C
- When applying to recently laid or grouted surfaces, wait for the adhesive or grout to cure completely.
- Thoroughly remove the product residues in order to avoid problems related to the oiliness of the surface.
- Before applying the product to the whole surface, it is advisable to test a small, unexposed area or unused piece to check its suitability for use.

EQUIPMENT CLEANING

At the end of the application, the equipment used can be washed using white spirit.

PHYSICAL-TECHNICAL DATA

Formula	<i>Liquid</i>
Color	<i>White</i>
Odor	<i>Unscented</i>
Specific gravity a 20°C	<i>991 ± 5 g/l</i>

STORAGE

Keep the container tightly closed and store in a cool, dry place.

SHELF LIFE

12 months in the original, sealed packaging, stored in a cool, dry place.

PACKAGING

1 l bottles – 12 bottles per box
5 l bottles – 4 bottles per box

MADE IN ITALY

100%

FABER CHIMICA SRL

60044 FABRIANO (AN) ITALY - VIA G. CERESANI 10 - LOC. CAMPO D'OLMO

PI-CF / VAT NUMBER 0100744021 - P: +39 0732 62 71 78

INFO@FABERSURFACECARE.COM - FABERSURFACECARE.COM



MADE4STONE

**SAFETY**

When applying the product, always use suitable personal protective equipment and follow the product safety data sheet instructions with care.

Rev. 0.0 – 27/07/2023

This technical data sheet supersedes all previous versions. Always refer to the latest version of the data sheet, available on www.fabersurfacecare.com site. Faber Chimica reserves the right to update and/or modify the data and information contained in the datasheet.

The information in this data sheet is based on our wide experience in technical and operational research. In any case, you should always make a preliminary test to verify the suitability of the product for the intended use and the type of material on which it will be applied. The information and the suggestions can't be construed as a commitment or result in our responsibility as the product's conditions and method of use cannot be controlled by us. Therefore Faber Chimica Srl disclaims any liability concerning the use of such data and suggestions.

MADE IN ITALY

100%