



MADE4STONE



## Protective treatments

### PACKED-S

## Solvent-based, Stain-resistant Color-enhancing Treatment for Low Absorbing Materials

**PACKED-S** is a solvent-based stain-resistant color-enhancing treatment formulated for compact and low-absorbing surfaces. Its use is recommended when in need to deepen the shade of porcelain slabs, quartz, and polished natural stone. The product doesn't create a film on the surface.

#### BENEFITS

- ✓ It provides high color-enhancing features
- ✓ Matt finish
- ✓ It won't yellow overtime
- ✓ Great stain-resistant properties

#### USES

**Suitable for** indoor and outdoor application.

**Suitable for** Granite, Limestone, Marble, Travertine, Craquelé Ceramic, Marble-resin agglomerates, Quartz-resin agglomerates, Glazed Porcelain Slabs, Natural porcelain slabs, Structured porcelain slabs, Basalt, Clinker.

#### COVERAGE

20/30 m<sup>2</sup>/l

#### APPLICATION EQUIPMENT

##### Product application:

Lambswool applicator, roller, cloth

#### APPLICATION STEPS

##### Surface preparation

- Thoroughly clean the surface making sure to remove all dust and dirt
- Do not apply **PACKED-S** on wet or humid surfaces
- Apply **PACKED-S** on surfaces with a temperature between +5 and +40°C
- Protect all areas not to be treated

##### Application

*Before applying the product is necessary to take a preliminary test on an unexposed area or unused piece of material to check the product's suitability.*

- On a clean and dry surface apply a thin and even layer of product using the preferred tool making sure to cover the whole surface.
- After 5-10 minutes from the application, before it is absorbed, proceed to even out the residues making sure to distribute them evenly in order to achieve a seamless result.
- After 20-30 minutes of the application proceed to thoroughly remove the residues in order to avoid all issues related to the oiliness of the product. This operation can be done using a cotton cloth. If the surface is quite large we recommend using a single disk machine or a hand polisher equipped with a wool pad or a felt pad.
- To maximize the efficacy of the product and to deepen the color of the surface it is possible to prolong the residue removal step beyond the 20-30 minutes to a maximum of 45-60 minutes. This will enable the product to settle deeper into the material. Attention: When waiting longer to remove the residues the removal process might be tougher.

MADE IN ITALY

100%



MADE4STONE



## APPLICATION STEPS

### Drying time

The product dries quickly within 1-2 hours from the application.

### Resume surface use

Resume surface use after 4-6 hours from the application.

## MAINTENANCE PRODUCTS

- For the daily cleaning of a surface treated with **PACKED-S** we recommend: **NEUGEL** or **ALGAFLOOR** depending on the material
- For the heavy-duty cleaning of a surface treated with **PACKED-S** we recommend: **FABER 30** o **DETERFUG** a depending on the material
- To dewax the surface we recommend using **DEC 21** e/o **DECERA/P**

## INSTRUCTIONS AND GUIDELINES

- Do not apply on wet or humid surfaces
- When used as a stain-resistant treatment on a surface previously treated with a water-resistant sealer, wait for the surface to be completely dry before applying **PACKED-S**
- Do not apply the product to overly heated surfaces
- Apply the product to surfaces with a temperature of between +5 and +40°C
- When applying to recently laid or grouted surfaces, wait for the adhesive or grout to cure completely.
- Thoroughly remove the product residues in order to avoid problems related to the oiliness of the surface.
- Before applying the product to the whole surface, it is advisable to test a small, unexposed area or unused piece to check its suitability for use.

## EQUIPMENT CLEANING

At the end of the application, the equipment used can be washed using white spirit.

## PHYSICAL-TECHNICAL DATA

Formula	<i>Liquid</i>
Color	<i>Clear</i>
Odor	<i>Solvent</i>
Flammability point (ASTM D 56)	<i>&lt;21°C</i>
Specific gravity a 20°C	<i>0,81 g/cm³</i>

## STORAGE

Keep the container tightly closed and store in a cool, dry place.

## SHELF LIFE

36 months in the original, sealed packaging, stored in a cool, dry place.

## PACKAGING

1 l bottles – 12 bottles per box  
5 l bottles – 4 bottles per box

## SAFETY

When applying the product, always use suitable personal protective equipment and follow the product safety data sheet instructions with care.

Rev. 0.0 – 27/07/2023

This technical data sheet supersedes all previous versions. Always refer to the latest version of the data sheet, available on [www.fabersurfacecare.com](http://www.fabersurfacecare.com) site. Faber Chimica reserves the right to update and/or modify the data and information contained in the datasheet.

The information in this data sheet is based on our wide experience in technical and operational research. In any case, you should always make a preliminary test to verify the suitability of the product for the intended use and the type of material on which it will be applied. The information and the suggestions can't be construed as a commitment or result in our responsibility as the product's conditions and method of use cannot be controlled by us. Therefore Faber Chimica Srl disclaims any liability concerning the use of such data and suggestions.