



MADE4STONE



Protective treatments

GUARD-S

Solvent-based, stain-resistant treatment for terracotta, natural stone, and agglomerates

GUARD-S is a solvent-based stain-resistant treatment. The product does not change the color of the material maintaining its natural look. This makes **GUARD-S** the ideal treatment to be applied on materials that are sensitive to color changes such as Limestone. It can also be applied in combination with a deep-penetrating water-resistant sealer.

BENEFITS

- ✓ Great stain-resistant properties
- ✓ UV resistant
- ✓ It preserves the natural look of the surface
- ✓ It won't yellow overtime

USES

Suitable for indoor and outdoor application.

Suitable for Marble, Sandstone, Limestone, Granite, Slate, Basaltina, Quartzite, Porphyry, Travertine, Cotto, Terracotta, Marble-resin agglomerate, Marble-concrete agglomerate, Quartz-resin agglomerate.

COVERAGE

10/15 m²/l

APPLICATION EQUIPMENT

Product application:

Lambswool applicator, roller, cloth

APPLICATION STEPS

Surface Preparation

- Thoroughly clean the surface making sure to remove all dust and dirt
- Do not apply **GUARD-S** on wet or humid surfaces
- Apply **GUARD-S** on surfaces with a temperature between +5 and +40°C
- Protect all areas, not to be treated

Application

Before applying the product is necessary to take a preliminary test on an unexposed area or unused piece of material to check the product's suitability.

- On a clean and dry surface apply a thin and even layer of product using the preferred tool making sure to cover the whole surface.
- The product dries quickly, residues can be easily removed using a dry clean cloth.
- In case of high absorbing materials we recommend applying a second coat of product. Make sure to wait at least 30 minutes in between applications.

Drying time

The product dries quickly within 40 minutes from the application.

Resume surface use

Resume surface use after 2-3 hours from the application.

MAINTENANCE PRODUCTS

- For the daily cleaning of a surface treated with **GUARD-S** we recommend: **NEUGEL** or **ALGAFLOOR** depending on the material
- For the heavy-duty cleaning of a surface treated with **GUARD-S** we recommend: **FABER 30** o **DETERFUG** a depending on the material

MADE IN ITALY

100%

FABER CHIMICA SRL

60044 FABRIANO (AN) ITALY - VIA G. CERESANI 10 - LOC. CAMPO D'OLMO

PI-CF / VAT NUMBER 0100744021 - P: +39 0732 62 71 78

INFO@FABERSURFACECARE.COM - FABERSURFACECARE.COM



MADE4STONE



INSTRUCTIONS AND GUIDELINES

- Do not apply on wet or humid surfaces
- When used as a stain-resistant treatment on a surface previously treated with a water-resistant sealer, wait for the surface to be completely dry before applying **GUARD -S**
- Do not apply the product to overly heated surfaces
- Apply the product to surfaces with a temperature of between +5 and +40°C
- When applying to recently laid or grouted surfaces, wait for the adhesive or grout to cure completely.
- Before applying the product to the whole surface, it is advisable to test a small, unexposed area or unused piece to check its suitability for use.

EQUIPMENT CLEANING

At the end of the application, the equipment used can be washed using white spirit.

PHYSICAL-TECHNICAL DATA

Formula	<i>Liquid</i>
Color	<i>Clear</i>
Odor	<i>Solvent</i>
Flammability point (ASTM D 56)	27°C
Specific gravity a 20°C	890 ± 10 g/l

STORAGE

Keep the container tightly closed and store in a cool, dry place.

SHELF LIFE

24 months in the original, sealed packaging, stored in a cool, dry place.

PACKAGING

1 l bottles – 12 bottles per box

SAFETY

When applying the product, always use suitable personal protective equipment and follow the product safety data sheet instructions with care.

Rev. 0.0 – 27/07/2023

This technical data sheet supersedes all previous versions. Always refer to the latest version of the data sheet, available on www.fabersurfacecare.com site. Faber Chimica reserves the right to update and/or modify the data and information contained in the datasheet.

The information in this data sheet is based on our wide experience in technical and operational research. In any case, you should always make a preliminary test to verify the suitability of the product for the intended use and the type of material on which it will be applied. The information and the suggestions can't be construed as a commitment or result in our responsibility as the product's conditions and method of use cannot be controlled by us. Therefore Faber Chimica Srl disclaims any liability concerning the use of such data and suggestions.

MADE IN ITALY

100%