

MADE4STONE



Protective treatments

W-STAIN

Water-based Stain-resistant Treatment with a Natural Finish for Agglomerates and Terracotta

W-STAIN is a water-based stain-resistant treatment for natural stones, agglomerates, and terracotta. **W-STAIN** is easy to apply, it doesn't create a film, and therefore, it doesn't change the breathability of the treated material. **W-STAIN** can be used as a stain-resistant treatment as a second step after a water-resistant deep penetrating sealer.

BENEFITS

- ✓ Good stain-resistant properties
- √ Water-based
- ✓ It won't yellow overtime
- ✓ It doesn't change the color of the treated material

USES

Suitable for indoor and outdoor application.

Suitable for Marble, Sandstone, Limestone, Granite, Slate, Basaltina, Quartzite, Porphyry, Travertine, Cotto, Terracotta, Marble-resin agglomerate,

Marble-cement agglomerate, Quartz-resin agglomerate

COVERAGE

15/20 m²/l

APPLICATION EQUIPMENT

Porduct application:

Brush, cloth, lambswool applicator

APPLICATION STEPS

Surface preparation

- Thoroughly clean the surface making sure to remove all dust and dirt
- Do not apply W-STAIN on wet or humid surfaces
- Apply W-STAIN on surfaces with a temberature between +5 and +40°C
- Protect all areas not tob e treated

Application

Before applying the product is necessary to take a preliminary test on an unexposed area or unused piece of material to check the product's suitability.

- On a clean and dry surface apply a thin and even layer of product using the preferred tool making sure to cover the whole surface.
- The product dries quickly. When applied on more compact and low absorbing
 materials residues of unabsorbed product might appear. In this case make
 sure to remove the residues using a dry and clean cloth. If the surface is highabsorbing a second coat of product can be applied after one hour from the
 first application.

Drvina time

The product dries quickly within 1 hour from the application.

Resume surface use

Resume surface use after 2-3 hours from the application.



MADE 4STONE



MAINTENANCE PRODUCTS

- For the daily cleaning of a surface treated with W-STAIN we recommend: NEUGEL or ALGAFLOOR depending on the material
- For the heavy-duty cleaning of a surface treated with W-STAIN we recommend: FABER 30 o DETERFUG a depending on the material

INSTRUCTIONS AND GUIDELINES

- Do not apply on wet or humid surfaces
- When used as a stain-resistant treatment on a surface previously treated with a water-resistant sealer, wait for the surface to be completely dry before applying W-STAIN
- Do not apply the product to overly heated surfaces
- Apply the product to surfaces with a temperature of between +5 and +40°C
- When applying to recently laid or grouted surfaces, wait for the adhesive or grout to cure completely.
- Before applying the product to the whole surface, it is advisable to test a small, unexposed area or unused piece to check its suitability for use.

EQUIPMENT CLEANING

At the end of the application, the equipment used can be washed using water

PHYSICAL-TECHNICAL DATA

Formula	Liquid
Color	Amber
Odor	Odorless
Flammability point (ASTM D 56)	<21°C
Specific gravity a 20°C	850 ± 10 g/l

STORAGE Keep the container tightly closed and store in a cool, dry place.

SHELF LIFE 24 months in the original, sealed packaging, stored in a cool, dry place.

PACKAGING 1 I bottles – 12 bottles per box

5 I bottles – 4 bottles per box

SAFETY When applying the product, always use suitable personal protective

equipment and follow the product safety data sheet instructions with

care.

Rev. 0.0 - 27/07/2023

This technical data sheet supersedes all previous versions. Always refer to the latest version of the data sheet, available on www.fabersurfacecare.com site. Faber Chimica reserves the right to update and/or modify the data and information contained in the datasheet.

The information in this data sheet is based on our wide experience in technical and operational research. In any case, you should always make a preliminary test to verify the suitability of the product for the intended use and the type of material on which it will be applied. The information and the suggestions can't be construed as a commitment or result in our responsibility as the product's conditions and method of use cannot be controlled by us. Therefore Faber Chimica Srl disclaims any liability concerning the use of such data and suggestions.