



PROFESSIONAL LINE



Finishing Products

HIDROFAB MATT

Protective dirt-resistant water-based wax with a matt finish

HIDROFAB MATT is a water-based self-leveling emulsion of resin and waxes to be used as a finishing treatment of floors made of natural stone, terracotta, concrete, structured porcelain tiles, and ceramic. The product fills the superficial crevices on which it is applied providing the surface with a softer finish to the touch. It also reduces the surface's ability to store dirt making daily maintenance easier. **HIDROFAB MATT** provides a matt finish and a slight increase in the tone of the material. The protective layer created by **HIDROFAB MATT** provides water and oil-resistant features and stain protection. **HIDROFAB MATT** is a product suitable for terracotta, concrete, concrete tiles, and concrete agglomerates. It can also be used on natural stone surfaces with rough finishes. The product can also be used on compact and low-absorbing surfaces characterized by rough textured like structured porcelain tiles.

BENEFITS

- ✓ Protection against dirt and stains
- ✓ It won't yellow overtime
- ✓ It makes maintenance easier
- ✓ It enhances the color of the material

USES

Suitable for indoor application.
Suitable for Terracotta, concrete, concrete tiles, concrete agglomerates, natural stone, and structured porcelain tiles.

COVERAGE

20/30 m²/Kg depending on how absorbing is the material

APPLICATION EQUIPMENT

Lambswool applicator, brush

APPLICATION STEPS

Surface Preparation

- Carefully clean the surface, making sure to remove any dust or dirt present
- Do not apply **HIDROFAB MATT** on a wet surface.
- Apply **HIDROFAB MATT** on surfaces with a temperature between +5 and +40°C
- Any adjacent surfaces not being treated with the product must be protected.

Application

Before applying the product is necessary to take a preliminary test of unexposed areas or unused pieces to check its suitability

- When applying the product on medium to high-absorbing surfaces it is recommended to previously apply a protective treatment
- When applying the product to low-absorbing materials it is possible to dilute it in water with a 1:1 ratio to facilitate the application.
- On a clean and dry surface apply a thin and even layer of product using the preferred tool. We recommend applying the product following the same application direction.
- Do not leave heavy residues on the surface during the application. Excess can be distributed as long as the product is still wet.
- When applying the product on high-absorbing surfaces or rough surfaces it could be necessary to apply a second coat. Wait 2-3 hours for the first layer to dry before applying the second one.

MADE IN ITALY

100%



PROFESSIONAL LINE



APPLICATION STEPS

- Apply the second coat following the instructions above crossing the application direction this time.

Drying Time

The product dries in 1-2 hours.

Resuming the surface use

Resume the surface use after 6-4 hours from the application.

MAINTENANCE PRODUCTS

For the daily cleaning of a surface treated with **HIDROFAB MATT** we recommend using the most suitable Faber cleaner such as **NEUTRAL CLEANER** o **FLOOR CLEANER**, to choose depending on the surface. For the maintenance of a surface treated with **HIDROFAB MATT** we recommend applying **HIDROFAB MATT** diluted 1:5

INSTRUCTIONS AND GUIDELINES

- Never apply the product to a wet surface
- Do not apply the product to overly heated surfaces
- Apply the product to surfaces with a temperature of between +5 and +40°C
- When applying to recently laid or grouted surfaces, wait for the adhesive or grout to cure completely.
- Do not apply on outdoor surfaces
- Before applying the product to the whole surface, it is advisable to test a small, unexposed area or unused piece to check its suitability for use.

EQUIPMENT CLEANING

At the end of application, the equipment used can be washed using water.

PHYSICAL-TECHNICAL DATA

Formula	Liquid
Color	White
Odor	Unscented
pH:	9,2 ± 0,6
Specific Gravity at 20°C	1018 ± 10 g/l

STORAGE

Keep the container tightly closed and store in a cool, dry place.

SHELF LIFE

24 months in the original, sealed packaging, stored in a cool, dry place.

PACKAGING

1 l bottle – 12 bottles per box
5 l bottle – 4 bottles per box

SAFETY

When applying the product, always use suitable personal protective equipment and follow the product safety data sheet instructions with care.

Rev. 0.0 – 31/03/2023

This technical data sheet supersedes all previous versions. Always refer to the latest version of the data sheet, available on www.fabersurfacecare.com site. Faber Chimica reserves the right to update and/or modify the data and information contained in the datasheet. The information in this data sheet is based on our wide experience in technical and operational research. In any case, you should always make a preliminary test to verify the suitability of the product for the intended use and the type of material on which it will be applied. The information and the suggestions can't be construed as a commitment or result in our responsibility as the conditions and method of use of the product cannot be controlled by us. Therefore Faber Chimica Srl disclaims any liability concerning the use of such data and suggestions.