


PROFESSIONAL LINE


Honing & Polishing

POLI-FX

Defects covering crystallizer

POLI-FX is a water-based defect-covering crystallizer for natural stone. The product allows quick and easy maintenance of the shine of surfaces while filling up and covering scratches and light defects. **POLI-FX** is recommended for the maintenance of the high-traffic floors.

BENEFITS	✓	High-coverage
	✓	Quick and easy to use
	✓	Highly compatible
	✓	Water-based

USES	This product is suitable for Marble, Granite, Travertine, Limestone, Terrazzo, Agglomerates
-------------	---

COVERAGE	30/40 m ² /kg
-----------------	--------------------------

APPLICATION EQUIPMENT	Single disc machine with at least 1.5 HP; manual polishing machine. Faber Chimica can supply the WARRIOR single disc machine, which has a power of 2.2 HP and is optimized for the correct application of any product.
------------------------------	--

APPLICATION STEPS *Surface preparation*

- Carefully clean the surface, making sure to remove any dust or dirt present.
- We suggest applying the product on surface sections of 1-2 m² at a time.
- Apply the product to surfaces with a temperature of between +5 and +40°C
- Any adjacent surfaces not being treated with the product must be protected.

Application

Before applying the product is necessary to take a preliminary test on an unexposed area or unused piece of material to check the product's suitability.

- Shake the bottle well, apply a spoon worth of product on the surface and start buffing the first section.
- Buff the product with a single-disk machine equipped with a white pad with rpm 150-200.
- Work the product in circular motions making sure to apply the product evenly throughout the whole section. As you apply the product we recommend broadening the movement towards the next section.
- Once the surface has been polished remove the dry residues using a cloth, a broom or a vacuum-cleaner.

To achieve a higher shine or superficial closure we recommend to repeat the application

The product doesn't give layering defects.

Resuming the surface use

After carefully removing any residues and rinsing the surface with water, the floor can be opened for use.

MADE IN ITALY

100%



PROFESSIONAL LINE



MAINTENANCE PRODUCTS

- For the daily maintenance of a surface treated with **POLI-FX**, we recommend: **ALGAFLOOR** or **NEUGEL** depending on the type of material
- For heavy-duty cleaning of a surface treated with **POLI-FX**, we recommend **FABER 30** or **DETERFUG**, according to the type of dirt and the material to be cleaned.

INSTRUCTIONS AND GUIDELINES

- Never apply the product to a wet surface
- Do not apply the product to overly heated surfaces
- Apply the product to surfaces with a temperature of between +5 and +40°C
- When applying to recently laid or grouted surfaces, wait for the adhesive or grout to cure completely.
- Before applying the product to the whole surface, it is advisable to test a small, unexposed area or unused piece to check its suitability for use.

EQUIPMENT CLEANING

At the end of application, the equipment used can be washed using water.

PHYSICAL-TECHNICAL DATA

Formula	Thick Liquid
Color	White
Odor	Unscented
pH:	3 ± 0,6
Specific gravity at 20°C	1010 ± 10 g/l

STORAGE

Keep the container tightly closed and store in a cool, dry place.

SHELF LIFE

24 months in the original, sealed packaging, stored in a cool, dry place.

PACKAGING

1 kg Bottle – 12 bottles per box
5 kg Bottle – 4 bottles per box

SAFETY

When applying the product, always use suitable personal protective equipment and follow the product safety data sheet instructions with care.

Revisione 0.0 – 05/09/2024

This technical data sheet supersedes all previous versions. Always refer to the latest version of the data sheet, available on www.fabersurfacecare.com site. Faber Chimica reserves the right to update and/or modify the data and information contained in the datasheet.

The information in this data sheet is based on our wide experience in technical and operational research. In any case, you should always make a preliminary test to verify the suitability of the product for the intended use and the type of material on which it will be applied. The information and the suggestions can't be construed as a commitment or result in our responsibility as the conditions and method of use of the product cannot be controlled by us. Therefore Faber Chimica Srl disclaims any liability concerning the use of such data and suggestions.