



PROFESSIONAL LINE



Protective Treatments

P 147 PLUS

Solvent-based, highly color-enhancing, stain-repellent, non-film-forming treatment with a matt finish for medium to highly absorbent substrates

P 147 PLUS is a solvent-based, stain-proof, highly color enhancing treatment. It is used to intensify the color of absorbent surfaces, giving a matt finish without generating a surface film. **P 147 PLUS** is indicated for the treatment of materials with a medium and medium-high degree of absorption. **P 147 PLUS** gives the support excellent stain-resistant properties, facilitating daily cleaning and maintenance.

BENEFITS

- ✓ UV resistant
- ✓ Certified safe for use on surfaces in contact with food
- ✓ Non filming treatment
- ✓ It won't yellow overtime

USES

Product suitable for application on: Marble-concrete agglomerate, Marble-resin agglomerate, Quartz-resin agglomerate, Slate, Sandstone, Basaltina - Lava stone, Molten basalt, Concrete tiles, Concrete, Granite, Limestone, Marble, Reconstructed stone (Ecopietra), Porphyry, Quartzite, Terracotta, Travertine, Tuff.

The product is not suitable for applications on polished surfaces.

COVERAGE

15/20 m²/l

APPLICATION EQUIPMENT

Brush, Lambswool applicator, Roller, Cloth

APPLICATION STEPS

Surface preparation

- Carefully clean the surface, making sure to remove any dust or dirt present.
- Never apply **P 147 PLUS** to wet or damp surfaces.
- Apply **P 147 PLUS** to surfaces with a temperature between +5 and +40°C
- Any surfaces in direct proximity not being treated must be protected.

Application

Before applying the product is necessary to take a preliminary test on an unexposed area or unused piece of material to check the product's suitability.

- Apply an even, coat of product to a clean, dry surface with the preferred tool, making sure to create an even layer to cover the whole surface being treated.
- About 5-10 minutes after the application, proceed to re-distribute the excess product using the same tool used for the application, making sure to cover the surface evenly.
- About 20-30 minutes after applying the product, remove all residues thoroughly, making sure all excesses have been removed to prevent any possible greasiness problem. This operation is performed by brushing the surface, dry, using a standard floor polisher (1.5 HP, 175 rpm) with a white or lambswool pad or wool-cotton attachment. Alternatively, residues can be removed with an orbital or manual wheel, using a white disc or pad, or a compact felt or wool-cotton cloth on tops, upright surfaces, or small areas.



PROFESSIONAL LINE



APPLICATION STEPS

- To maximize the effectiveness of the stain-proofing treatment, the intensity of the color-enhancer, and the durability of the treatment, it is possible to wait over 20-30 minutes, up to a maximum of 45-60 minutes, before removing residues, to allow the product to penetrate fully and deep down inside the structure of more compact materials. This way, the surface residues may be slightly harder to remove.

Drying Time

The product dries quickly, within 1-2 hours of the application.

Resume Surface Use

Resume the use of the surface after 4-6 hours from the application

MAINTENANCE PRODUCTS

- For the daily cleaning of a surface treated with **P 147 PLUS**, we recommend: **NEUGEL** or **ALGAFLOOR**
- For heavy-duty cleaning of a surface treated with **P 147 PLUS**, we recommend: **FABER 30** or **DETERFUG** according to the type of material
- To remove **P 147 PLUS** we recommend: **DEC 21** and/or **DECERA/P** depending on the material .

INSTRUCTIONS AND GUIDELINES

- Never apply the product to wet or damp surfaces.
- If the product is applied as a stain-proof treatment on a material that has already been primed with a high penetrating water-repellent sealer, wait for this to dry completely before applying **P 147 PLUS**.
- Do not apply the product to overly heated surfaces.
- Do not apply on polished surfaces.
- Do not apply the product when there is an imminent risk of rain or frost or in the presence of mist, fog, or high levels of humidity.
- Apply the product to surfaces with a temperature of between +5 and +35°C
- When applying to recently laid or grouted surfaces, wait for the adhesive or grout to cure completely.
- Before applying the product to the whole surface, it is advisable to test a small, unexposed area or unused piece to check its suitability for use.

EQUIPMENT CLEANING

At the end of the application, the equipment used can be washed using white spirit.

PHYSICAL-TECHNICAL DATA

Formula	Liquid
Color	Clear
Odor	Solvent
Specific gravity a 20°C	908 ± 10 g/l
Flash Point (ASTM D 56)	< 23°C

STORAGE

Keep the container tightly closed and store in a cool, dry place.

SHELF LIFE

24 months in the original, sealed packaging, stored in a cool, dry place.

PACKAGING

1 l bottles – 12 bottles per box
5 l bottles – 4 bottles per box

MADE IN ITALY

100%

FABER CHIMICA SRL

60044 FABRIANO (AN) ITALY - VIA G. CERESANI 10 - LOC. CAMPO D'OLMO

PI-CF / VAT NUMBER 0100744021 - P: +39 0732 62 71 78

INFO@FABERSURFACECARE.COM - FABERSURFACECARE.COM

**PROFESSIONAL LINE****SAFETY**

When applying the product, always use suitable personal protective equipment and follow the product safety data sheet instructions with care.

Revisione 1.0 – 30/06/2025

This technical data sheet supersedes all previous versions. Always refer to the latest version of the data sheet, available on www.fabersurfacecare.com site. Faber Chimica reserves the right to update and/or modify the data and information contained in the datasheet.

The information in this data sheet is based on our wide experience in technical and operational research. In any case, you should always make a preliminary test to verify the suitability of the product for the intended use and the type of material on which it will be applied. The information and the suggestions can't be construed as a commitment or result in our responsibility as the conditions and method of use of the product cannot be controlled by us. Therefore Faber Chimica Srl disclaims any liability concerning the use of such data and suggestions.

MADE IN ITALY

100%