



MADE4STONE

**Finishing Product****H2O SOLID WAX****Water-based paste wax, easy to apply for polishing natural stone tops and slabs**

**H2O SOLID WAX** is a water-based wax to be used for polishing non-walkable surfaces such as walls and worktops. The product polishes and enhances the tone and aesthetic characteristics of the material on which it is applied, masking the defects of the polishing process.

**BENEFITS**

- ✓ Easy application
- ✓ Water-based formula
- ✓ It enhances the shade and brightness of the material
- ✓ It won't yellow overtime

**USES**

**Suitable for** indoor applications.  
**Suitable for** Marble and natural stone surfaces.

**COVERAGE**20/30 g/m<sup>2</sup>**APPLICATION EQUIPMENT**

**Product application:**  
 Cloth, white pad

**Product polishing:**

Hand polisher, single disk machine equipped with steel-wool pad

**APPLICATION STEPS****Surface Preparation**

- Thoroughly clean the surface making sure to remove all dust and dirt
- Do not apply **H2O SOLID WAX** on wet or humid surfaces
- In order to increase product penetration the surface can be heated
- Protect all areas, not to be treated

**Application**

*Before applying the product is necessary to take a preliminary test on an unexposed area or unused piece of material to check the product's suitability.*

- On a dry and clean surface, apply an even layer of product using the tool of your choice, making sure to cover the entire surface.
- Let it dry for a minimum of 10 minutes and a maximum of 40-60 minutes.
- Polish the product using a hand-polisher (max 1500 rpm) equipped with a steel wool pad.
- Let it dry for approximately 12 hours.
- If the surface loses its shine over time, it can be easily restored by reapplying the product and polishing it with steel wool, even manually.

**MAINTENANCE PRODUCTS**

- To dewax a surface treated with **H2O SOLID WAX** we recommend: **FABER 30 2.0**

**INSTRUCTIONS AND GUIDELINES**

- Do not apply on wet or humid surfaces
- Protect all areas not to be treated
- When applying to recently laid or grouted surfaces, wait for the adhesive or grout to cure completely.

MADE IN ITALY

100%



MADE4STONE



## INSTRUCTIONS AND GUIDELINES

- Before applying the product to the whole surface, it is advisable to test a small, unexposed area or unused piece to check its suitability for use.
- Once the surface has been polished we recommend waiting at least 12 hours before using cleaners.

## EQUIPMENT CLEANING

At the end of the application, the equipment used can be washed using water.

## PHYSICAL-TECHNICAL DATA

Formula	<i>Creamy formula</i>
Color	<i>Beige</i>
Odor	<i>Flowery scent</i>
Specific gravity a 20°C	<i>1000 ± 10 g/l</i>
pH	<i>5,5 ± 0,5</i>

## STORAGE

Keep the container tightly closed and store in a cool, dry place.

## SHELF LIFE

12 months in the original, sealed packaging, stored in a cool, dry place.

## SAFETY

When applying the product, always use suitable personal protective equipment and follow the product safety data sheet instructions with care.

Rev. 0.0 – 15/09/2025

This technical data sheet supersedes all previous versions. Always refer to the latest version of the data sheet, available on [www.fabersurfacecare.com](http://www.fabersurfacecare.com) site. Faber Chimica reserves the right to update and/or modify the data and information contained in the datasheet.

The information in this data sheet is based on our wide experience in technical and operational research. In any case, you should always make a preliminary test to verify the suitability of the product for the intended use and the type of material on which it will be applied. The information and the suggestions can't be construed as a commitment or result in our responsibility as the product's conditions and method of use cannot be controlled by us. Therefore Faber Chimica Srl disclaims any liability concerning the use of such data and suggestions.

MADE IN ITALY

100%